

MATERIAL SAFETY DATA SHEET

MegaPower MP 95 Engine Treatment

MSDS Number: MP 95 Engine Treatment

Version Number: 1

Version Date: 1/2/2010

MEGA POWER

8565A Somerset Drive Largo, FL 33773-2712 Tel: 813-855-6664 MSDS on-line: www.MegaPower.com

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product/Chemical Name: Product Description: Chemical Family: CAS Registry: Manufacturer: Mega Power MP 95 Engine Treatment Engine Additive Mixture

MEGA POWER 8565A Somerset Drive Largo, FL 33773-2712 813-855-6664

SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS			
INGREDIENT	CAS No	WT. RANGE %	EXPOSURE LIMIT
Hydrotreated petroleum distillate	64742-54-7	89-96	5mg/cubic meter as mist
Chlorinated alkane C14-17	63449-39-8	3-6	Not Established
Methyl Ester	67784-80-9	1-5	Not Established

*Hazardous according to OSHA (1910.1200) or one or more state Right-to-Know lists.

	OLU	TION 3 – HAZARDOUS IDENTIFICATION	
Health:	0		HMIS
Flammability:	1		
Reactivity:	0		H H
Special:	None		F R
0 = minimal 1= slight 2=mode	erate 3= serio	bus 4= severe	PPE [†]
Route(s) of Entry			† _{Sec. 8}
Inhalation:	Yes		
Skin:	Yes		
Ingestion:	Yes		
Eyes:	Yes		
Target Organs:			
Effects of overexposure:			
Acute:	Eyes:	May cause minimal irritation, exp	erienced as temporary discom

©2010 MEGA POWER

--- FOR DISCLAIMER OF LIABILITY SEE FINAL PAGE ---

Effects of overexposure (con't)	Skin:	Brief contact is not irritating. Prolonged contact, as with clothing wetted with material may cause defatting of skin or irritation, seen as local	
Acute:		redness with possible mild discomfort. Other than the potential skin irritation effects noted above, acute (short term) adverse effects are not expected from brief skin contact.	
	Inhalation:	Vapors or mist, in excess of permissible concentrations, or in unusually high concentrations generated from spraying, heating the material or as from exposure in poorly ventilated areas or confined spaces, may cause irritation of the nose and throat, headache, nausea, and drowsiness. Prolonged or repeated overexposure may result in the absorption of potentially harmful amounts of material.	
Sensitization Properties:	Ingestion: Unknown	May cause irritation, nausea, and vomiting.	
Signs and Symptoms of Exposure:	See above "E	bove "Effects of Overexposure."	
Medical Conditions Generally Aggravated by Long-Term Exposure: Chronic Effects:			
Carcinogenicity NTP: IARC Monographs: OSHA Regulations: ACGIH	Not listed Not listed Not listed Not listed		
	SECT	TION 4 – FIRST AID MEASURES	
Emergency and First Aid Procedures:	Eye contact:	Immediately flush with large quantities of water for at least 15 minutes and	
	Skin contact	Remove excess with cloth or paper towel. Wash thoroughly with soap and water. If irritation persists, get medical attention.	
	Ingestion:	Immediately contact a physician, poison control center or emergency treatment center. DO NOT induce vomiting. Aspiration Hazard: Product may be inhaled into lungs if vomited.	
	Inhalation:	Remove to fresh air. Restore and/or support breathing as required. Keep victim warm and at rest.	
Note to Physicians: Special Precautions/Procedure		nptomatically	

SECTION 5 - FIRE-FIGHTING MEASURES

©2010 MEGA POWER

Unusual Fire Fighting procedures: Flash Point:	None known 350 F NFPA
Flash Point Method:	Closed Cup
Burning Rate:	Unknown
Autoignition Temperature:	Unknown $\langle 0 \times 0 \rangle$
Flammable limits in air (% by volume):	Unknown
LEL:	Not determined
UEL:	Not determined
Flammability Classification:	Combustible
Extinguishing Media:	Use water spray, dry chemical, foam or carbon dioxide to extinguish.
Unusual Fire or Explosion Hazards:	None known
Fire-Fighting Instructions;	According to the National Fire Protection Association Guide, use water spray,
	dry chemical, foam or carbon dioxide. Water or foam may cause frothing.
	Use water spray to disperse the vapors and to provide protection for person
Fire-Fighting Equipment:	attempting to stop the leak. Because fire may produce toxic thermal decomposition products, wear a self-
	contained breathing apparatus (SCBA) with a full facepiece operated in
	pressure-demand or positive-pressure mode.
Unusual Fire Fighting procedures:	Not required
Other Information:	Products evolved when subjected to heat or combustion: Carbon Monoxide
	and Carbon Dioxide may be formed on burning in limited air supply.
Secti	ON 6 – ACCIDENTAL RELEASE MEASURES
Spill/Leak Procedures:	Wear appropriate personal protective equipment, including appropriate
	respiratory protection. Contain spill if possible. Wipe up or absorb on suitable
	material and shovel up. Prevent entry into sewers and waterways. Avoid
Regulatory Requirements:	contact with skin, eyes or clothing.
	ECTION 7 – HANDLING AND STORAGE
Handling Precautions Storage Requirements:	Minimum feasible handling temperatures should be maintained.
Storage Requirements:	Periods of exposure to high temperature should be minimized. Water contamination should be avoided. Do not store near food.
	EXPOSURE CONTROLS/PERSONAL PROTECTION
	Normal to maintain exposure below TLV
Permissible Concentrations in Air:	Supplied air reapiratory protection for cleaning large spille or upon entry inte
	Supplied air respiratory protection for cleaning large spills or upon entry into tanks, vessels, or other confined spaces. Use a NIOSH approved organic vapor
	and gas respirator with mist filter.
	Chemical type goggles or face shield.
	Wear chemically protective gloves, boots, aprons, and gauntlets to prevent
	prolonged or repeated skin contact. Wear protective eyeglasses or chemical
	safety goggles.
	Exposed employees should exercise reasonable personal cleanliness; this
	includes cleansing exposed skin areas several times daily with soap and water,
	and laundering or dry cleaning soiled work clothing at least weekly.
	Make emergency eyewash stations, safety/quick-drench showers, and washing
	facilities available in work area.

Contaminated Equipment:	Separate contaminated work clothes from street clothes. Launder before reuse.
	Remove this material from your shoes and clean personal protective equipment.
Comments:	Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

©2010 MEGA POWER

--- FOR DISCLAIMER OF LIABILITY SEE FINAL PAGE ---

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Clear Liquid, bland odor

Appearance and odor:
Boiling Point (760 mm Hg):
Freezing/Melting Point:
Specific Gravity (water =1):
Vapor Density (air =1):
Percent Volatile by Volume:
Evaporation Rate (butyl acetate =1):
Solubility in Water (% by wt):
Vapor Pressure (at 20°C):
pH:
Viscosity SUS @ 100⁰F

20 F 0.86 >1 0 Nil Not Soluble <1 n/a 110

No data

SECTION 10 - STABILITY AND REACTIVITY

Stability: Polymerization: Chemical Incompatibilities: Conditions to Avoid: Hazardous decomposition products: Stable Does not occur Strong oxidizers, acids Exposure to heat, sparks, or open flames. Carbon dioxide, carbon monoxide

SECTION 11 – TOXICOLOGICAL INFORMATION

Eye Effects: Skin Effects: Acute Inhalation Effects: Acute Oral Effects: Chronic Effects: Carcinogenicity: Mutagenicity: Teratogenicity: Mildly irritationg. Mildly irritating. No information available. No information available. Unknown Neither product nor its ingredients are listed by IARC, NTD or OSHA Not mutagenic Not Teratogenic

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity:

Soil Absorption/Mobility:

Experimental studies show that acute aquatic toxicity values are greater than 1000 mg/l.

Volatilization to air is not expected to be a significant fate process due to the low vapor pressure of this material. In water, base oils will float and spread over the surface at a rate dependent upon viscosity. There will be significant removal of hydrocarbons from the water by sediment adsorption. In soil and sediment, hydrocarbon components will show low mobility with adsorption to sediments being the predominant physical process. The main fate process is expected to be slow biodegradation of base oil components in soil and sediment.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal Method:	Dispose of waste in accordance with Federal, State and Local laws.
Disposal Regulatory Requirements:	Under RCRA, it is the responsibility of the user of products to determine, at
	the time of disposal, whether product meets RCRA criteria for hazardous
	waste. This is because product uses transformations, mixture, processes,
	etc., may render the resulting material hazardous (see waste classification)
Container Cleaning and Disposal:	Containers should be cleaned of residual product before disposal, and
	disposed of in accordance with all applicable laws and regulations.

©2010 MEGA POWER

--- FOR DISCLAIMER OF LIABILITY SEE FINAL PAGE ---

	SECTION 14 – TRA	NSPORT INFORMATION
DOT Shipping Name:	Not regulated	
Shipping Symbols:	Not applicable	
Hazard Class: DOT Identification No.:	Not applicable	
Packing Group:	Not applicable	
Label:	Not applicable	
Special Provisions (172.102):	Not applicable	
Packaging Authorizations		
a) Exceptions:	Not applicable	
b) Non-bulk Packaging:c) Bulk Packaging:	Not applicable	
	Not applicable	
Quantity Limitations a) Passenger, Aircraft, or Railcar:	Not applicable	
b) Cargo Aircraft Only:	Not applicable	
Vessel Stowage Requirements		
a) Vessel Stowage:	Not applicable	
b) Other:	Not applicable	
S	ECTION 15 - REGI	JLATORY INFORMATION
EPA Regulations		
RCRA Hazardous Waste Number and	RCRA	
Hazardous Waste Classification:		Unused product is not classified as a hazardous waste by RCRA criteria
CERCLA Hazardous Substance and C	CERCLA	
Reportable Quantity:		Does not contain any ingredients listed as a CERCLA
		hazardous substance.
CADA Tavia Chamical and CADA FUG	.	Contains following substance which is listed in Title III.
SARA Toxic Chemical and SARA EHS:		Contains following substance which is listed in Title III: SARA 313 Information:
		SARA Hazard Category:
OSHA Regulations:		
State Regulations:		
Other:		All components listed on both TSCA (USA) and DSL
		(Canada) inventory.
	0-0-0-0	
		THER INFORMATION
Prepared By: MEGA POWER		
Additional Hazard Rating Systems: None Disclaimer: THE INFORMATION GIVEN HEREIN IS GIVEN IN GOOD FAITH AND FROM SOURCES WE BELIEVE		
		ED, REGARDING ITS CORRECTNESS IS MADE.
The conditions or methods of handling.	storage. use and di	sposal of this product are beyond our control and may be
		not assume responsibility and expressly disclaim liability for
loss, damage or expense arising out of	or in any way conne	ected with the handling, storage, use or disposal of this

This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not apply.

CONSULT MEGA POWER FOR FURTHER INFORMATION.

©2010 MEGA POWER

product.

MSDS: MP 95 Engine Treatment

--- FOR DISCLAIMER OF LIABILITY SEE FINAL PAGE ---